

The contour map:





R

Ceiling speaker system

installation :

1. Cut a hole with a diameter of Φ 175mm in the ceiling.



3. The product is clamped to the mounting plane by clamps.



2. Connect the audio cable and pull back the clip.



4. The installation is complete.





The appearance is for reference only, please refer to the real object

Product Performance Standards:GB/T 12060.5-2011 Manufacturer: Guangzhou Ruifeng Digital Technology Co., Ltd. Address: No. 10, Shilou Section, Shilian Road, Shilou Town, Panyu District, Guangzhou

www.lax-pro.com

* This manual is for reference only and is subject to change without prior notice

Ceiling speaker system

Series application:

A place in a shop, department store, school, office, hotel, restaurant

Product characteristics:


The beautiful white coating and white mesh cover are used on the surface. The stylish and exquisite appearance can be perfectly integrated with the modern interior decoration.

The panel is made of high strength iron material, which is solid, durable and reliable.

The internal design of the system can provide professional sound performance, reflecting extraordinary speech and music reproduction effect.

Simple and convenient power setting, easy to operate. Suitable for many occasions.

Wiring diagram:



Technical parameters:

Frequency Response	80Hz ~ 15kHz
Sensitivity(1M/1W)	89±3dB
Nominal resistance	1.6kΩ(6W)/3.3kΩ(3W)
Rated power	6W
Power tap	6W/3W (100V)
The loudest pressure level	96dB
Dimension(L*W*H)	Ф200*65mm
Unit Weight	0.63kg

Product curve chart:

